



# ATOM

Fixed gas detector

ATOM series of gas detectors is explosion-proof and designed for continuous monitoring of hazardous concentrations of flammable, toxic gases, volatile organic compounds (VOC) and oxygen (O<sub>2</sub>) in the air of the working area.





## Features and benefits

- Applied sensor types: PID, LEL, EC, MEMS and IR (hydrocarbons, CO2);
- Detection of the presence of output signals: 4-20 mA and HART;
- Ability to detect a sensor on another type;
- Temperature and ambient range from -60°C to +65°C;
- LED status indicator (work, error, service); Bright OLED display for display and menu access;
- Settings and parameters are available: magnetic key, HART, Bluetooth\*, UART (for service connection);
- Two holes for cable entry M20 / M25.

## SMART-sensor

- Non-volatile memory of the SMART sensor for storing settings;
  - The built-in temperature sensor provides adaptive heating of the SMART sensor.
- 3 years warranty
  - 20 years service life

\* Optional

**Gases** Explosive gases, toxic gases, oxygen

**Temperature Range** -60°C to +65°C

**Ex marking** 1 Ex d IIC T6 Gb X

**Ingress Protection** IP66, IP68, IP69

**Supply Voltage** 24V (nominal) Range: 16-36V

**Communication**  
OLED-display  
4-20 mA  
HART  
Bluetooth\*

**Permissible Humidity** < 98% (non-condensing)

**Operating Pressure** 80 - 120 kPa

**Measurement Mode** < 2 W

**Nominal Settling Time Of The Output Signal At The Level T0.9**  
10 sec IR  
15 sec LEL, MEMS  
30 sec EC  
30 sec PID

**Gas Analyzer Warm-up Time Limit, no more**  
10 min IR, PID  
60 min LEL, EC  
20 min MEMS

**Mean time between failures**  
100000 h IR  
35000 h LEL, EC, PID  
70000 h MEMS

**Customization**  
Magnetic key  
Bluetooth\*  
HART  
USB-UART adapter for PC


**Material** Aluminum alloy, stainless steel 316L

**Dimensions** 156x120x105 mm


**Weight** 2 kg (aluminum alloy), 3,9 kg (stainless steel)

## Modifications


ATOM-MEMS with semiconductor sensor



ATOM-IR with infrared sensor




ATOM-LEL with thermocatalytic sensor



ATOM PID with photoionization sensor



ATOM-EC with electrochemical sensor




\*Optional

## Accessories



- 01. Anti-vandal protection
- 02. Insect guard
- 03. Calibration nozzle
- 04. Protective visor from the sun and precipitation
- 05. Pipe mounting kit (pipe diameter 38-68 mm)
- 06. Duct mounting kit

## Fast and convenient installation



- 01. Type of mounting for pipe mounting
- 02. Mounting type for wall mounting
- 03. Type of fastening for installation in an air duct



[www.mirax-safety.com](http://www.mirax-safety.com)